

MilCAM Recon[®] III LocatIR

LONG RANGE, LIGHT WEIGHT THERMAL
BINOCULAR WITH GEO LOCATION



APPLICATIONS

- RECONNAISSANCE
- SURVEILLANCE
- OPERATOR GEO-LOCATION
- TARGET GEO-LOCATION
- SITUATIONAL AWARENESS
- BATTLE DAMAGE ASSESSMENT
- FORCE PROTECTION

FEATURES

- High resolution, large format 640x480 mid-wave InSb sensor
- Instant-on, long-wave channel
- Fast 3 field of view system with 15, 10, and 2.5 degree fields of view and digital zoom
- Internal Global Positioning Sensor (GPS) and Digital Magnetic Compass (DMC) and modular Laser Rangefinder (LRF)
- Laser pointer options
- Flexible remote control, power, and video options
- Lightweight and rugged, Mil STD 810-F qualified
- New automatic digital image processing techniques
- Runs for over 4 hours on D cell Lithium batteries
- Modular design for future upgrades
- It's all FLIR inside

BENEFITS

- Delivers unmatched range performance and image quality
- Provides fast situational awareness and a redundant sensor
- Perfectly matched zoom settings for the short, medium, and long range reconnaissance mission
- Provides precision geo-location of targets with eye safe laser rangefinder
- Offer additional tactical advantage when coupled with night vision equipment
- Can be configured for tripod use with full remote control for continuous operation with video output
- Reduces operator fatigue for long duration missions without sacrificing field hardening
- Offers image detail unmatched by analog systems
- Get long run times on commercially available batteries
- Offers mission flexibility and customization based on your requirements
- FLIR controls the entire supply chain on the critical technology inside MilCAM Recon systems, ensuring fast service and long term support



High sensitivity thermal imagery



Long range optics aid in identification





MilCAM Recon[®] III LocatIR

THERMAL IMAGING PERFORMANCE

Sensor type	640 x 480 InSb and 320 x 240 VOx Microbolometer
Number of fields of view	3
Wide FOV	15.0° h x 11.3° v
Medium FOV	10.0° h x 8.0° v
Narrow FOV	2.5° h x 1.8° v
E-zoom	2x, 4x
Spectral band	3-5, 8-12 µm
Automatic features	Auto focus, AGC, Digital Detail Enhancement (DDE)

SYSTEM FEATURES

Global Positioning System (GPS)	C/A code (supports military GPS plug-in)
Digital Magnetic Compass	0.3° accuracy
Eyesafe Laser Rangefinder (LRF)	Detachable, 1.54 µm, > 5 km

OUTPUTS

Video	NTSC/PAL Video, S video, optional DVI
Connector types	BNC, S Video

POWER

Power requirements	7 VDC/ 5.5 W (9 V to 32 VDC external)
Battery type and life	4.5 hours continuous (D cell Lithium)

ENVIRONMENTAL

Mil-Spec	MIL STD 810-F
Operating temp	-32°C to 55°C (-26°F to 131°F)

DIMENSIONS, WEIGHT & MOUNTING

Dimensions	22.2 x 24.9 x 8.3 cm (8.75" x 9.8" x 3.25")
Weight	<2.95 kg (6.5 lb.)
Mounting	Tripod mount 1/4-20 base

INTERFACES

Command and Control	RS 232/422
---------------------	------------

STANDARD PACKAGE

Storage/transport Case	Hard shell, lockable with fitted foam insert
Adapter/charger	110 VAC/220 VAC power supply
Batteries	4 each, Lithium D cells
Lens cleaning kit	Complete cleaning kit in nylon pouch
Operator's manual	Covers operation and operator-level maintenance
Cables	Video cable, 3 m with BNC connectors

OPTIONS

Laser pointer	830nm Class 3B 30mW
Laser pointer	830nm Class 3B 150mW
Soft case	Lightweight with padded zippered compartments

CORPORATE HEADQUARTERS

FLIR Systems, Inc.
27700A SW Parkway Ave.
Wilsonville, OR 97070
USA
PH: +1 800.727.3547

BOSTON

FLIR Systems Boston, Inc.
25 Esquire Road
North Billerica, MA 01862
USA
PH: +1 800.464.6372

SANTA BARBARA

FLIR Systems, Inc.
Indigo Operations
70 Castilian Dr.
Goleta, CA 93117
USA
PH: +1 888.747.3547

EUROPE

FLIR Systems Ltd.
2 Kings Hill Avenue
West Malling, Kent
ME19 4AQ
United Kingdom
PH: +44.1732.220011

CANADA

FLIR Systems Ltd.
5230 South Service Road
Suite 125
Burlington, ON L7L 5K2
Canada
PH: +1 800.613.0507

SWEDEN

FLIR Systems AB
Rinkebyvagen 19
P.O. Box 3
SE-182 11 Danderyd
Sweden
PH: +46.8.753.2500

MIDDLE EAST

FLIR Systems, Inc.
c/o Middle East Optronics
FZCO
Unit C-13
Dubai Airport Free Zone
P.O. Box 54262
Dubai
United Arab Emirates
PH: +9714.299.6898

www.flir.com